



KÖSTER Primer BL

Solvent free, polymer-modified bitumen based strongly adhesive primer for KSK membranes and Polymer Modified Bitumen Coatings

Features

KÖSTER Primer BL is a solvent free, polymer-modified bitumen based strongly adhesive primer for KSK membranes and Polymer Modified Bitumen Coatings such as KÖSTER Bikuthan 1C. It is characterized by very good adhesion to dry and slightly moist mineral substrates.

Technical Data

Solid particle content	greater than 55 %
Minimum application temperature	+ 5 °C
Curing time (at + 20 °C)	24 hours
Application of next layer:	
at + 20 °C	after approx. 3 - 4 hours
at + 10 °C	after approx. 5 - 7 hours

Fields of Application

KÖSTER Primer BL is a primer for preparing substrates for the application of KÖSTER KSK membranes and KÖSTER Polymer Modified Bitumen Coatings such as KÖSTER Deuxan, KÖSTER Bikuthan.

Substrate

The substrate has to be a mineral substrate (no gypsum) and must be dry, free of loose particles, dust, oil, and grease.

Application

When used as a primer under KÖSTER KSK Membranes, KÖSTER Primer BL is applied thoroughly undiluted in one coat using a roller, brush, or a suitable spraying device. When used as a primer under Polymer Modified Bitumen Coatings such as KÖSTER Bikuthan 1C, KÖSTER Primer BL is applied diluted 1:5 parts by weight with water and applied with a brush, roller, or spraying device.

Consumption

Approx. 150 - 300 g / m²

In case of strongly absorbent substrates, two coats may be necessary (total consumption approx. 500 g / m²)

Cleaning

Clean tools immediately after use with clean water. In hardened state, remove the material mechanically and then clean with KÖSTER Universal Cleaner.

Packaging

W 120 015 15 kg bucket

Storage

Store the material cool but frost free. In originally sealed containers it can be stored for a minimum of 12 months.

Safety

Observe all governmental, state, and local safety regulations when processing the material.

Related products

KÖSTER Bikuthan 1C
KÖSTER Fix-Tape 10 ALU
KÖSTER Butyl Fix-Tape Fleece
KÖSTER KSK ALU 15
KÖSTER KSK SY 15
KÖSTER Universal Cleaner

Prod. code W 251 030
Prod. code W 810 AL
Prod. code W 815 015 F
Prod. code W 815 096 AL
Prod. code W 815 105
Prod. code X 910 010

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.